

# A1 Electrical Enclosure

## IP-A804030

**ALUMINIUM | SINGLE DOOR | IP66**

**800H x 400W x 300D**

**IP Enclosures A1 range of marine grade aluminium electrical enclosures are suitable for general industrial applications.**

**Protection:** Complies with IP66

**Standard:** IEC62208, IEC/EN/AS60529

**Material:**

- Body: Marine Grade Aluminium
- Door: Marine Grade Aluminium
- Device Mounting Plate: 1.5mm galvanised steel sheet
- Seal: Polyurethane

**Body:** The robust monoblock body is fabricated using marine grade aluminium. Flat face sealing surfaces are provided to increase seal life. Integral device plate mounts, M6 earth studs and welded mounting feet are incorporated. Cutting, pressing and full continuous seam welding using precision automated manufacturing equipment ensures accuracy and consistent high quality.

**Single Door:** The robust surface mounted door is fabricated using marine grade aluminium and incorporates concealed removable hinges with captive pins. The door is designed for a 110° opening. Each door contains an M6 earth stud and a high quality machine-applied foamed in place (FIP) Polyurethane seal.

**Seal:** A high quality machine-applied full perimeter UL listed Polyurethane seal foamed in place (FIP) provides excellent sealing over a long life. Temperature resistance -40°C to 80°C (160°C short term loading).

**Lock:** Stainless Steel 8mm square drive quarter turn lock with key. A full range of locking solutions are available upon request.

**Device Mounting Plate:** The device mounting plate is fabricated using 1.5mm galvanised steel sheet, pressed to provide additional strength and supplied pre-fitted into enclosure as standard.

**Surface Treatment:** UL approved epoxy polyester powder-coated with a textured finish. 80-120 micron average thickness. Colour RAL7035.

